

DSpeaker

Anti-Mode X2 configuration file loaded.

Please remember to click the "Save" button when you're finished!

Save

Miscellaneous

Crossover Frequency	80 ▾	Hz
Infrasonic Filter	20 ▾	Hz
Automatic Standby When Idle	Off ▾	
Volume Control via USB *) (See below)	<input type="checkbox"/>	

*) Allows volume control from a computer connected to the USB port. Enabling this setting can cause a sudden increase in volume. Please use with caution!

Parametric EQ

Bass Adjust Cutoff			Treble Adjust Cutoff		
•		80 Hz			12000 Hz
••		120 Hz			8000 Hz
•••		200 Hz			4000 Hz
••••		320 Hz			2000 Hz
•••••		500 Hz			1500 Hz

PEQ Bandwidth			
•		2 Q	0.71 oct
••		1.42 Q	1 oct
•••		1 Q	1.39 oct
••••		0.71 Q	1.89 oct
•••••		0.5 Q	2.54 oct

Input Volume Trim

Analog Input Trim		12 dB	
Optical Input Trim		0 dB	
Coaxial Input Trim		0 dB	
USB Input Trim		0 dB	

Channel Delay

Left Channel Delay		auto	
Right Channel Delay		auto	

(Subwoofer output channel is always minimum latency)